

TIMANTTI 7

Durable and washable topcoat for high-traffic areas

TIMANTTI 7 is the ideal choice for spaces that require extra durability. This high-performance topcoat provides outstanding washability and a refined matt finish, making it perfect for high-traffic areas such as kitchens, bathrooms, hallways, staircases, schools, hospitals, food processing facilities and similar spaces.



TIMANTTI 7 contains a mildew-resistant agent that protects the paint surface and makes it suitable for use in humid areas such as bathrooms and changing rooms.

Designed to resist moisture, mildew, and chemicals, TIMANTTI 7 is easy to clean - even with disinfectant - helping to maintain a hygienic environment. It can also be tinted with Teknos Interior colours to create the desired atmosphere.



TECHNICAL DATA

Certificates, approvals and classification	M1 classification, Finnish Key Flag
Fields of application	Ceilings, Indoor wall
Recommended substrate	Pre-primed boards, Concrete, Building board, Filler, Gypsum board, Acrylate paint
Solids	Approx. 41% by volume
Volatile organic compound (VOC)	EU VOC limit value (cat A/a): 30 g/l. Base paint 1 contains max. 9 g/l, Base paint 3 contains max. 24 g/l.
Theoretical spreading rate	8 m ² /l.
Practical spreading rate	The quality of the substrate and the chosen application method affect the practical spreading rate.
Colours	Base paints 1 (white) and 3, which can be tinted to obtain the shades in Interior Colour Card. Ready-made shade: Off-white T1724 (T1327).
Tinting system	Teknomix
Gloss (60°)	Matt, gloss approx. 7 (at 60° angle).
Thinner	Water.
Density	Approx. 1.3 g/ml
Storage	Must not freeze.

Packaging

Base paints 1 and 3: 0.9 l, 2.7 l, 9 l, 18 l.

Off-white T1724 (T1327): 18 l.

Availability varies by country.

DIRECTION FOR USE**Surface preparation**

Clean new surfaces from dust and dirt. Wash previously painted surfaces with RENSA SUPER paint cleaner. Matt down hard or gloss surfaces by sanding and thereafter remove the dust. For smoothing of irregularities in the surface choose a suitable filler from the SILORA series. The dried filler is sanded down and the dust removed.

Priming

HUMID AREAS: Prime concrete, plaster, filler, brick, and building board surfaces with TIMANTTI W moisture sealer according to the directions for use.

IN DRY AREAS prime the surfaces previously mentioned with TIMANTTI 3 Primer.

Application method

Brush, Roller, Spray

Suitable airless nozzle size 0.017 - 0.021".

Application

Stir thoroughly before use.

Application conditions

The surface to be treated must be dry. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +10°C and the relative air humidity below 80%. Drying is faster in low air humidity and/or above +21°C. Application will be easier if air is humidified and/or temperature is lowered in the working space. Ventilation after the painting will quicken the drying.

Thinning

The paint can be diluted with water, if required, but dilution may impair the coverage of the paint.

Drying time

+23°C / 50% RH

- dust free

1 h

- overcoatable

2 h

The drying process will be slower in cold and/or damp.

Washability and wear resistance

Wear resistance of the painted surface is very good.

The painted surface can be washed repeatedly.

Wet scrub resistance: class 1, according to EN 13300 (ISO 11998).

Cleaning

Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

HEALTH AND SAFETY**Safety and precaution measures**

See safety data sheet.

ADDITIONAL INFORMATION

Maintenance instructions

The final forming of the film takes approx. 4 weeks under normal circumstances and after that the ultimate durability and hardness is reached. Before this the surface must be treated with care.

The surface can be cleaned by wiping with a neutral (pH 6 - 8) detergent. For very dirty surfaces can also alkalinescent (pH 8 - 10) detergents be used. Detergent and dirt are removed by wiping and/or rinsing the surface with clean water. Use a cleaning cloth, soft sponge or similar for cleaning. Avoid coarse brushing or heavy abrasion. Follow the dilution and other instructions of the detergent producer when using detergents.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.